

TECHNICAL SPECIFICATIONS

MODELS	IST8-1-LI	IST8-2-LI	IST8-3-LI
INPUT			
VOLTAGE (VAC)	120-295		
FREQUENCY (HZ)	50/60± 10% (50/60Hz)		
POWER FACTOR	≥0.99		
THDI	<5%		
OUTPUT			
POWER (W/VA)	1000/1000	2000/2000	3000/3000
MAX. AC/AC EFFICIENCY	92.7%	93.5%	96%
POWER FACTOR	1		
VOLTAGE (VAC)	208/220/230/240±1%		
FREQUENCY (HZ)	50/60±0.1		
THD	<3%		
SWITCHING TIME (MS)	0		
ECO MODE	Yes		
OVERLOAD	101%~115% for 1 min, 116%~133% for 1 s, < 134% for 200ms		
LITHIUM BATTERIES			
VOLTAGE (VDC)	24	48	72
BACKUP TIME (MIN)	11	11	11
MAX. CHARGING CURRENT (A)	4		
OTHER SPECIFICATION			
COMMUNICATIONS	USB and SNMP (slot) (RS232+ Optional dry contact card)		
OUTPUT SOCKETS	(8) 5-15R	(6) 5-20R	(4) 5-20R + (1) L5-30R
DISPLAY	LCD		
PROTECTIONS	Low batteries, Overload, Short-circuit, Over-temperature, ecc.		
NOISE (DB)	< 55		
TEMPERATURE	0°C~60°C		
HUMIDITY	0 ~ 95%		
DIMENSIONS (L×W×H) (MM)	438×420×87	438×570×87	438×570×87
WEIGHT (KG)	8.9	13.6	196
STANDARDS AND CERTIFICATIONS	CE (Reference standards: Safety IEC EN 62040-1; EMC IEC EN 62040-2; Classification IEC EN 62040-3)		

ALL INFORMATION IS INDICATIVE, MAY BE MODIFIED BY AEC AT ANY TIME AND DOES NOT CONSTITUTE CONTRACTUAL OBLIGATIONS.

YOUTUBE VIDEO TUTORIAL



ASSISTANCE 24\7 ON ALL SOCIAL NETWORK

